



Code	I400-SCE
Output	6.1kW
Log length	255mm
Nett efficiency	77.1%
Width	405mm
Height	558mm
Depth	407mm

The newly improved, sleek and cutting-edge design of the i Series makes these cassette stoves perfect for the modern, energy-conscious household.

Complete with heat convection system, easy-to-use controls and tertiary burn system, the i Series will get the most from your fuel. Our range of colour finishes will ensure your i Series stove fits perfectly into your home, whilst the internal pre-heated airwash system keeps your glass crystal clear for a warming view of the fire.

Features

- Lifetime guarantee
- Pre-heated airwash system for sparkling clean glass
- Stainless steel ash pan
- Burns wood or solid fuel
- Optional choice of trim size and colour
- Optional choice of door colours
- Radiant and convected heat
- Flexifuel System
- Primary and secondary burn to improve efficiency
- Top flue fitting 127mm (5")
- Internal flue fitting for ease of installation
- Approved for use in Smoke Control Areas

Optional Extras

- 60mm Trim for i400 - [TRIM004]
- Arada Ash Carrier - Small - [ARA016]
- Trim For I400 3 Sided - Standard(30mm) - [TRIM014]
- Trim For I400 3 Sided - Wide (60mm) - [TRIM026]
- Trim For I400 4 Sided - Standard (30mm) - [TRIM020]
- Trim For I400 4 Sided - Wide (60mm) - [TRIM032]

i400 - Technical Information

Code	I400-SCE
Output range	2-8kW
Nett efficiency	77.1 %
Width	405mm
Height	558mm
Depth	407mm
Width in fireplace	405mm
Height in fireplace	556mm
Depth into fireplace	351mm
Depth of back to centre of top flue	100mm
Flue diameter	127mm
Flue outlet	Vertical Spigot
Suitable for 12mm hearth	No
Under hearth temperature	119.1°C
Suitable for direct air supply kit	No
Packed weight	59kg
Maximum log length	255mm

Minimum Distance To Combustibles

To rear of stove	220 mm
To sides of stove	220 mm
Above stove	250 mm

