

# Ecoburn Plus 5 Inset



Code	ECB5FPLUS-INSET
Output	4.8kW
Log length	200mm
Nett efficiency	80.1%
Width	536mm
Height	590mm
Depth	362mm

The inset version of our ever-popular Ecoburn<sup>Plus</sup> stove has been designed to provide a convenient solution for converting an open fire into a high performance fireplace. Complete with the same large viewing glass and clean lines, our Ecoburn<sup>Plus</sup> Inset is the perfect modern heating option.

## Features

- Lifetime guarantee
- Pre-heated airwash system for sparkling clean glass
- Stainless steel ash pan
- Burns wood or solid fuel
- Externally controlled riddling grate
- Fits into standard British fireplace opening
- Large fire viewing window
- Flexifuel System
- Primary and secondary burn to improve efficiency
- No need to remove the chair brick (5kW model)

## Optional Extras

- Arada Ash Carrier - Small - [ARA016]
- Long Reach Flue Gather - [5INSETGATHER-LONG]
- Standard Flue Gather - [5INSETGATHER]



## Ecoburn Plus 5 Inset - Technical Information

Code	ECB5FPLUS- INSET
Output range	1-6kW
Nett efficiency	80.1 %
Width	536mm
Height	590mm
Depth	362mm
Depth of front fascia	172mm
Width in fireplace	375mm
Height in fireplace	535mm
Width tapers down to	278mm
Depth into fireplace	190mm
Flue diameter	127mm
Flue outlet	Letterbox style
Suitable for 12mm hearth	No
Under hearth temperature	127°C
Suitable for direct air supply kit	No
Packed weight	68kg
Maximum log length	200mm

## Minimum Distance To Combustibles

To sides of stove	200 mm
Above stove	300 mm



Arada Ltd, The Fireworks, Weycroft Avenue, Axminster, Devon. EX13 5HU. | Tel: +44 (0)1297 35700 (Mon-Fri 8:30am-5pm)

Web: <http://www.aradastoves.com> | Email: [info@aradastoves.com](mailto:info@aradastoves.com) Printed 15th February 2016. Technical information updated 22nd September 2014.